



**Built to last!**

**Construction Tools  
Range Overview**

# Table of Contents

## Pneumatic Equipment

|                               |    |
|-------------------------------|----|
| Breakers                      | 4  |
| Spike Drivers                 | 7  |
| Pick Hammers                  | 8  |
| Clay Diggers                  | 11 |
| Chipping Hammers              | 12 |
| River Busters                 | 17 |
| Rotary Hammers                | 18 |
| Sinkers / Surface Rock Drills | 20 |
| Core Drill                    | 22 |
| Scabblers                     | 22 |
| Saw                           | 23 |
| Pumps                         | 23 |

## Hydraulic Equipment

|              |    |
|--------------|----|
| Power Packs  | 26 |
| Pick Hammers | 27 |
| Breakers     | 28 |
| Cut-off Saw  | 32 |
| Core Drill   | 32 |
| Pumps        | 33 |

## Petrol-driven Equipment

|         |    |
|---------|----|
| Breaker | 36 |
|---------|----|

## Compaction Equipment

|                                 |    |
|---------------------------------|----|
| Forward Soil and Asphalt Plates | 38 |
| Walk Behind Double Drum Roller  | 40 |
| Forward and Reversible Plates   | 40 |
| Vibrator                        | 42 |
| Tampers                         | 43 |

## Rig-mounted Equipment

|                    |    |
|--------------------|----|
| Hydraulic Breakers | 46 |
|--------------------|----|

## Compressors

|                      |    |
|----------------------|----|
| Portable Compressors | 52 |
|----------------------|----|

## Generators

|                     |    |
|---------------------|----|
| Portable Generators | 56 |
|---------------------|----|

## Light tower

|                      |    |
|----------------------|----|
| Portable light tower | 60 |
|----------------------|----|

**Important:** Full details of sound and vibration measurement stated in the tables are available in the Safety and Operating Instructions of the product. It can be found on [www.cpprintshop.com](http://www.cpprintshop.com)



**Pneumatic Equipment**

## Breakers



| MODEL                                                  | CP 0112*     | CP 0112 S    | CP 0112 EX*  |
|--------------------------------------------------------|--------------|--------------|--------------|
| WEIGHT (kg)                                            | 13.5         | 14.5         | 16           |
| LENGTH (mm)                                            | 535          | 535          | 800          |
| AIR CONSUMPTION (l/s)                                  | 23           | 23           | 23           |
| BLOWS PER MINUTE (bpm)                                 | 1620         | 1620         | 1620         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> |              | 16.3         |              |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     |              | 105          |              |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             |              | 93           |              |
| CHUCK SIZE (mm)                                        | 25 x 108     | 25 x 108     | 25 x 108     |
| PART NUMBER                                            | 8900 0030 23 | 8900 0030 25 | 8900 0030 24 |

\*Not sold within EU / EEA



| MODEL                                                  | CP 0117*                                                                 | CP 0117 S                                                                |
|--------------------------------------------------------|--------------------------------------------------------------------------|--------------------------------------------------------------------------|
| WEIGHT (kg)                                            | 35                                                                       | 36                                                                       |
| LENGTH (mm)                                            | 740                                                                      | 740                                                                      |
| AIR CONSUMPTION (l/s)                                  | 35                                                                       | 35                                                                       |
| BLOWS PER MINUTE (bpm)                                 | 1080                                                                     | 1080                                                                     |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> |                                                                          | 11.9                                                                     |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     |                                                                          | 108                                                                      |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             |                                                                          | 95                                                                       |
| CHUCK SIZE (mm)                                        | see part number                                                          | see part number                                                          |
| PART NUMBER                                            | <b>T022090</b><br>(28 x 160 chuck)<br><b>T022091</b><br>(32 x 160 chuck) | <b>T022093</b><br>(28 x 160 chuck)<br><b>T022092</b><br>(32 x 160 chuck) |

\*Not sold within EU / EEA



| MODEL                                                  | CP 1210*                             | CP 1210 S                            | CP 1210 S                        |
|--------------------------------------------------------|--------------------------------------|--------------------------------------|----------------------------------|
| WEIGHT (kg)                                            | 20                                   | 22                                   | 22.5                             |
| LENGTH (mm)                                            | 540                                  | 540                                  | 585                              |
| AIR CONSUMPTION (l/s)                                  | 26.5                                 | 26.5                                 | 26.5                             |
| BLOWS PER MINUTE (bpm)                                 | 1400                                 | 1400                                 | 1400                             |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> |                                      | 14.6                                 | 14.6                             |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     |                                      | 105                                  | 105                              |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             |                                      | 92                                   | 92                               |
| CHUCK SIZE (mm)                                        | 25 x 108                             | 25 x 108                             | see part number                  |
| PART NUMBER                                            | 8900 0030 01<br>(N American shank)   | 8900 0030 03<br>(N American shank)   | 8900 0030 07<br>(28 x 160 chuck) |
|                                                        | 8900 0030 02<br>(ISO standard shank) | 8900 0030 04<br>(ISO standard shank) | 8900 0030 09<br>(32 x 160 chuck) |

\*Not sold within EU / EEA



| MODEL                                                  | CP 1210 SVR                                             | CP 1210 SVR                      |
|--------------------------------------------------------|---------------------------------------------------------|----------------------------------|
| WEIGHT (kg)                                            | 24.5                                                    | 25                               |
| LENGTH (mm)                                            | 600                                                     | 650                              |
| AIR CONSUMPTION (l/s)                                  | 26.5                                                    | 26.5                             |
| BLOWS PER MINUTE (bpm)                                 | 1400                                                    | 1400                             |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 5.3                                                     | 5.3                              |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 105                                                     | 105                              |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 92                                                      | 92                               |
| CHUCK SIZE (mm)                                        | see part number                                         | see part number                  |
| PART NUMBER                                            | 8900 0030 05<br>(25 x 108 chuck,<br>N American shank)   | 8900 0030 08<br>(28 x 160 chuck) |
|                                                        | 8900 0030 06<br>(25 x 108 chuck,<br>ISO standard shank) | 8900 0030 10<br>(32 x 160 chuck) |

## Breakers



| MODEL                                                  | CP 1230*                           | CP 1230 S                          | CP 1230 SVR                        |
|--------------------------------------------------------|------------------------------------|------------------------------------|------------------------------------|
| WEIGHT (kg)                                            | 29.5                               | 31                                 | 34.5                               |
| LENGTH (mm)                                            | 680                                | 680                                | 730                                |
| AIR CONSUMPTION (l/s)                                  | 32                                 | 32                                 | 32                                 |
| BLOWS PER MINUTE (bpm)                                 | 1300                               | 1300                               | 1300                               |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> |                                    | 18.2                               | 7.4                                |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     |                                    | 108                                | 108                                |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             |                                    | 95                                 | 95                                 |
| CHUCK SIZE (mm)                                        | see part number                    | see part number                    | see part number                    |
| PART NUMBER                                            | <b>T022073</b><br>(28 x 160 chuck) | <b>T022158</b><br>(28 x 160 chuck) | <b>T024227</b><br>(28 x 160 chuck) |
|                                                        | <b>T022074</b><br>(32 x 160 chuck) | <b>T022159</b><br>(32 x 160 chuck) | <b>T024239</b><br>(32 x 160 chuck) |

\*Not sold within EU / EEA



| MODEL                                                  | CP 1240*                           | CP 1240 S                          | CP 1240 SVR                        |
|--------------------------------------------------------|------------------------------------|------------------------------------|------------------------------------|
| WEIGHT (kg)                                            | 37.5                               | 39                                 | 43                                 |
| LENGTH (mm)                                            | 735                                | 735                                | 785                                |
| AIR CONSUMPTION (l/s)                                  | 40                                 | 40                                 | 40                                 |
| BLOWS PER MINUTE (bpm)                                 | 1150                               | 1150                               | 1150                               |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> |                                    | 15.3                               | 7.8                                |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     |                                    | 111                                | 111                                |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             |                                    | 98                                 | 99                                 |
| CHUCK SIZE (mm)                                        | see part number                    | see part number                    | see part number                    |
| PART NUMBER                                            | <b>T022075</b><br>(28 x 160 chuck) | <b>T022221</b><br>(28 x 160 chuck) | <b>T024536</b><br>(28 x 160 chuck) |
|                                                        | <b>T022076</b><br>(32 x 160 chuck) | <b>T022222</b><br>(32 x 160 chuck) | <b>T024535</b><br>(32 x 160 chuck) |

\*Not sold within EU / EEA

## Spike Drivers

| MODEL                                                  | CP 1230 SPDR* | CP 1230 S SPDR |
|--------------------------------------------------------|---------------|----------------|
| WEIGHT (kg)                                            | 28.5          | 30             |
| LENGTH (mm)                                            | 625           | 625            |
| AIR CONSUMPTION (l/s)                                  | 32            | 32             |
| BLOWS PER MINUTE (bpm)                                 | 1300          | 1300           |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> |               | 18.2           |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     |               | 108            |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             |               | 95             |
| CHUCK SIZE (mm)                                        | N/A           | N/A            |
| PART NUMBER                                            | T021612       | T021613        |

\*Not sold within EU / EEA



| MODEL                                                  | CP 1240 SPDR* | CP 1240 S SPDR |
|--------------------------------------------------------|---------------|----------------|
| WEIGHT (kg)                                            | 37            | 38.5           |
| LENGTH (mm)                                            | 665           | 665            |
| AIR CONSUMPTION (l/s)                                  | 40            | 40             |
| BLOWS PER MINUTE (bpm)                                 | 1150          | 1150           |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> |               | 15.3           |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     |               | 111            |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             |               | 98             |
| CHUCK SIZE (mm)                                        | N/A           | N/A            |
| PART NUMBER                                            | T021042       | T021041        |

\*Not sold within EU / EEA

## Pick Hammers



| MODEL                                                  | CP 0111 CHLA* | CP 0111 CHIT* |
|--------------------------------------------------------|---------------|---------------|
| WEIGHT (kg)                                            | 11            | 13            |
| LENGTH (mm)                                            | 560           | 560           |
| AIR CONSUMPTION (l/s)                                  | 21            | 21            |
| BLOWS PER MINUTE (bpm)                                 | 1800          | 1800          |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> |               |               |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     |               |               |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             |               |               |
| CHUCK SIZE (mm)                                        | Hex 25 x 108  | Hex 22 x 82.5 |
| PART NUMBER                                            | 8900 0001 20  | 8900 0001 41  |

\*Not sold within EU / EEA



| MODEL                                                  | CP 0122 S     | CP 0122 SL    |
|--------------------------------------------------------|---------------|---------------|
| WEIGHT (kg)                                            | 11            | 13            |
| LENGTH (mm)                                            | 565           | 560           |
| AIR CONSUMPTION (l/s)                                  | 22            | 22            |
| BLOWS PER MINUTE (bpm)                                 | 1380          | 1380          |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 16.3          | 16.3          |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 105           | 105           |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 89            | 93            |
| CHUCK SIZE (mm)                                        | Hex 22 x 82.5 | Hex 22 x 82.5 |
| PART NUMBER                                            | 8900 0001 43  | 8900 0001 48  |



| MODEL                                                  | CP 0122 SVR   | CP 0122 SVR  |
|--------------------------------------------------------|---------------|--------------|
| WEIGHT (kg)                                            | 13.5          | 13.5         |
| LENGTH (mm)                                            | 665           | 665          |
| AIR CONSUMPTION (l/s)                                  | 21            | 21           |
| BLOWS PER MINUTE (bpm)                                 | 1380          | 1380         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 21.9          | 21.9         |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 105           | 105          |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 89            | 89           |
| CHUCK SIZE (mm)                                        | Hex 22 x 82.5 | Rd 25 x 75   |
| PART NUMBER                                            | 8900 0001 45  | 8900 0001 44 |



| MODEL                                                  | CP 0125 S    | CP 0125 SVR  |
|--------------------------------------------------------|--------------|--------------|
| WEIGHT (kg)                                            | 12.5         | 14           |
| LENGTH (mm)                                            | 630          | 730          |
| AIR CONSUMPTION (l/s)                                  | 17           | 17           |
| BLOWS PER MINUTE (bpm)                                 | 1080         | 1080         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 28.7         | 30.1         |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 105          | 105          |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 91           | 91           |
| CHUCK SIZE (mm)                                        | Rd 25 x 75   | Rd 25 x 75   |
| PART NUMBER                                            | 8900 0001 46 | 8900 0001 47 |

# Pick Hammers



| MODEL                                                  | CP 0222 CHIT* | CP 0222 CHITBS | CP 0222 CHOTBS |
|--------------------------------------------------------|---------------|----------------|----------------|
| WEIGHT (kg)                                            | 10            | 11             | 11             |
| LENGTH (mm)                                            | 510           | 510            | 510            |
| AIR CONSUMPTION (l/s)                                  | 19            | 19             | 19             |
| BLOWS PER MINUTE (bpm)                                 | 1500          | 1500           | 1500           |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> |               | 19.8           | 19.8           |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     |               | 105            | 105            |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             |               | 90             | 90             |
| CHUCK SIZE (mm)                                        | Hex 22 x 82.5 | Hex 22 x 82.5  | Hex 22 x 82.5  |
| PART NUMBER                                            | 8900 0001 21  | 8900 0001 22   | 8900 0001 23   |

\*Not sold within EU / EEA



| MODEL                                                  | FL 0022 S    |
|--------------------------------------------------------|--------------|
| WEIGHT (kg)                                            | 10.5         |
| LENGTH (mm)                                            | 495          |
| AIR CONSUMPTION (l/s)                                  | 22           |
| BLOWS PER MINUTE (bpm)                                 | 1380         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 16.3         |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 105          |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 89           |
| CHUCK SIZE (mm)                                        | Rd 25 x 75   |
| PART NUMBER                                            | 8900 0001 42 |

\*Not sold within EU / EEA

# Clay Diggers



| MODEL                                                  | FL 0022      | FL 0022 S    |
|--------------------------------------------------------|--------------|--------------|
| WEIGHT (kg)                                            | 10.5         | 11           |
| LENGTH (mm)                                            | 495          | 495          |
| AIR CONSUMPTION (l/s)                                  | 22           | 22           |
| BLOWS PER MINUTE (bpm)                                 | 1380         | 1380         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 16.3         | 16.3         |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | -            | 105          |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | -            | 89           |
| CHUCK SIZE (mm)                                        | Sq 19 x 82   | Sq 19 x 82   |
| PART NUMBER                                            | 8900 0001 24 | 8900 0001 25 |



| MODEL                                                  | FL 0022 SVR  | FL 0022 VR |
|--------------------------------------------------------|--------------|------------|
| WEIGHT (kg)                                            | 13           | 12.5       |
| LENGTH (mm)                                            | 635          | 635        |
| AIR CONSUMPTION (l/s)                                  | 21           | 21         |
| BLOWS PER MINUTE (bpm)                                 | 1380         | 1380       |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 21.9         | 21.9       |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 105          | -          |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 89           | -          |
| CHUCK SIZE (mm)                                        | Sq 19 x 82   | Sq 19 x 82 |
| PART NUMBER                                            | 8900 0001 39 | T025402    |

## Chipping Hammers



| MODEL                                                  | CP 0012 19X50 | CP 0012 2R   | CP 0012 2H   |
|--------------------------------------------------------|---------------|--------------|--------------|
| WEIGHT (kg)                                            | 5.5           | 5.5          | 5.5          |
| LENGTH (mm)                                            | 406           | 406          | 406          |
| AIR CONSUMPTION (l/s)                                  | 9.5           | 9.5          | 9.5          |
| BLOWS PER MINUTE (bpm)                                 | 2600          | 2600         | 2600         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 14.6          | 14.6         | 14.6         |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 104           | 104          | 104          |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 89            | 89           | 89           |
| CHUCK SIZE (mm)                                        | Hex 19 x 50   | Rd 17.3      | Hex 14.7     |
| PART NUMBER                                            | 8900 0001 01  | 8900 0001 02 | 8900 0001 03 |



| MODEL                                                  | CP 0016 19x50 |
|--------------------------------------------------------|---------------|
| WEIGHT (kg)                                            | 8.5           |
| LENGTH (mm)                                            | 420           |
| AIR CONSUMPTION (l/s)                                  | 12            |
| BLOWS PER MINUTE (bpm)                                 | 1920          |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 9.6           |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 104           |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 91            |
| CHUCK SIZE (mm)                                        | Hex 19 x 50   |
| PART NUMBER                                            | 8900 0001 32  |



| MODEL                                                  | CP 0017 SVR<br>19 x 50 | CP 0017 SVR<br>3R | CP 0017 SVR<br>3H |
|--------------------------------------------------------|------------------------|-------------------|-------------------|
| WEIGHT (kg)                                            | 9.5                    | 9.5               | 9.5               |
| LENGTH (mm)                                            | 540                    | 535               | 535               |
| AIR CONSUMPTION (l/s)                                  | 17                     | 17                | 17                |
| BLOWS PER MINUTE (bpm)                                 | 1770                   | 1770              | 1770              |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 12.4                   | 12.4              | 12.4              |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 104                    | 104               | 104               |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 90                     | 90                | 90                |
| CHUCK SIZE (mm)                                        | Hex 19 x 50            | Rd 17.3           | Hex 14.7          |
| PART NUMBER                                            | 8900 0001 35           | 8900 0001 36      | 8900 0001 37      |



| MODEL                                                  | CP 4123 2R*  | CP 4123 2R*  | CP 4123 3R*  |
|--------------------------------------------------------|--------------|--------------|--------------|
| WEIGHT (kg)                                            | 7            | 7            | 7.5          |
| LENGTH (mm)                                            | 375          | 375          | 425          |
| AIR CONSUMPTION (l/s)                                  | 12           | 12           | 14           |
| BLOWS PER MINUTE (bpm)                                 | 2200         | 2220         | 1800         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 13.2         | 13.2         | 11.4         |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     |              |              |              |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             |              |              |              |
| CHUCK SIZE (mm)                                        | Rd 17.3      | Hex 14.7     | Rd 17.3      |
| PART NUMBER                                            | 8900 0001 04 | 8900 0001 05 | 8900 0001 06 |

\*Not sold within EU / EEA

## Chipping Hammers



| MODEL                                                  | CP 4123 3H*  | CP 4123 4R*  | CP 4123 4H*  |
|--------------------------------------------------------|--------------|--------------|--------------|
| WEIGHT (kg)                                            | 7.5          | 8            | 8            |
| LENGTH (mm)                                            | 425          | 460          | 460          |
| AIR CONSUMPTION (l/s)                                  | 14           | 13           | 13           |
| BLOWS PER MINUTE (bpm)                                 | 1800         | 1440         | 1440         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 11.4         | 13.9         | 13.9         |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     |              |              |              |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             |              |              |              |
| CHUCK SIZE (mm)                                        | Hex 14.7     | Rd 17.3      | Hex 14.7     |
| PART NUMBER                                            | 8900 0001 07 | 8900 0001 08 | 8900 0001 09 |

\*Not sold within EU / EEA



| MODEL                                                  | CP 4125 2R*  | CP 4125 2H*  | CP 4125 3R*  |
|--------------------------------------------------------|--------------|--------------|--------------|
| WEIGHT (kg)                                            | 7            | 7            | 7.5          |
| LENGTH (mm)                                            | 380          | 380          | 415          |
| AIR CONSUMPTION (l/s)                                  | 13           | 13           | 15           |
| BLOWS PER MINUTE (bpm)                                 | 1920         | 1920         | 1680         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 13.8         | 13.8         | 15.3         |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     |              |              |              |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             |              |              |              |
| CHUCK SIZE (mm)                                        | Rd 17.3      | Hex 14.7     | Rd 17.3      |
| PART NUMBER                                            | 8900 0001 10 | 8900 0001 11 | 8900 0001 12 |

\*Not sold within EU / EEA



| MODEL                                                  | CP 4125 3H*  | CP 4125 4R*  | CP 4125 4H*  |
|--------------------------------------------------------|--------------|--------------|--------------|
| WEIGHT (kg)                                            | 7.5          | 8            | 8            |
| LENGTH (mm)                                            | 415          | 445          | 445          |
| AIR CONSUMPTION (l/s)                                  | 15           | 13           | 13           |
| BLOWS PER MINUTE (bpm)                                 | 1680         | 1440         | 1440         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 15.3         | 14.6         | 14.6         |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     |              |              |              |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             |              |              |              |
| CHUCK SIZE (mm)                                        | Hex 14.7     | Rd 17.3      | Hex 14.7     |
| PART NUMBER                                            | 8900 0001 13 | 8900 0001 14 | 8900 0001 15 |

\*Not sold within EU / EEA



| MODEL                                                  | CP 4130 3R   | CP 4130 3H   |
|--------------------------------------------------------|--------------|--------------|
| WEIGHT (kg)                                            | 8.5          | 8.5          |
| LENGTH (mm)                                            | 420          | 420          |
| AIR CONSUMPTION (l/s)                                  | 12           | 12           |
| BLOWS PER MINUTE (bpm)                                 | 1920         | 1920         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 9.6          | 9.6          |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 104          | 104          |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 90           | 90           |
| CHUCK SIZE (mm)                                        | Rd 17.3      | Hex 14.7     |
| PART NUMBER                                            | 8900 0001 16 | 8900 0001 17 |

## Chipping Hammers



| MODEL                                                  | CP 4130 4R   | CP 4130 4H   |
|--------------------------------------------------------|--------------|--------------|
| WEIGHT (kg)                                            | 9            | 9            |
| LENGTH (mm)                                            | 450          | 450          |
| AIR CONSUMPTION (l/s)                                  | 12.5         | 12.5         |
| BLOWS PER MINUTE (bpm)                                 | 1440         | 1440         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 12.3         | 12.3         |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 104          | 104          |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 90           | 90           |
| CHUCK SIZE (mm)                                        | Rd 17.3      | Hex 14.7     |
| PART NUMBER                                            | 8900 0001 18 | 8900 0001 19 |



| MODEL                                                  | CP 4131 3R   | CP 4131 3H   |
|--------------------------------------------------------|--------------|--------------|
| WEIGHT (kg)                                            | 9            | 9            |
| LENGTH (mm)                                            | 420          | 420          |
| AIR CONSUMPTION (l/s)                                  | 12           | 12           |
| BLOWS PER MINUTE (bpm)                                 | 1920         | 1920         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 9.6          | 9.6          |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 104          | 104          |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 91           | 91           |
| CHUCK SIZE (mm)                                        | Rd 17.3      | Hex 14.7     |
| PART NUMBER                                            | 8900 0001 33 | 8900 0001 34 |

## Rivet Busters



| MODEL                                                  | CP 4608 P    | CP 4608 D    |
|--------------------------------------------------------|--------------|--------------|
| WEIGHT (kg)                                            | 13.5         | 14           |
| LENGTH (mm)                                            | 585          | 600          |
| AIR CONSUMPTION (l/s)                                  | 21           | 21           |
| BLOWS PER MINUTE (bpm)                                 | 900          | 900          |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 12.6         | 12.3         |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 105          | 105          |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 93           | 93           |
| CHUCK SIZE                                             | Jumbo        | Jumbo        |
| PART NUMBER                                            | 8900 0001 49 | 8900 0001 51 |



| MODEL                                                  | CP 4611 P    | CP 4611 D    |
|--------------------------------------------------------|--------------|--------------|
| WEIGHT (kg)                                            | 15           | 15.5         |
| LENGTH (mm)                                            | 660          | 675          |
| AIR CONSUMPTION (l/s)                                  | 21           | 21           |
| BLOWS PER MINUTE (bpm)                                 | 720          | 720          |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 13.3         | 14.3         |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 105          | 105          |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 93           | 93           |
| CHUCK SIZE                                             | Jumbo        | Jumbo        |
| PART NUMBER                                            | 8900 0001 50 | 8900 0001 52 |

## Rotary Hammers



| MODEL                                                                            | CP 0009 A*  | CP 0009 AC* | CP 0009 CS  |
|----------------------------------------------------------------------------------|-------------|-------------|-------------|
| WEIGHT (kg)                                                                      | 4           | 4           | 4.5         |
| LENGTH (mm)                                                                      | 375         | 375         | 375         |
| AIR CONSUMPTION (l/s)                                                            | 9           | 9           | 9           |
| BLOWS PER MINUTE (bpm)                                                           | 3420        | 3420        | 3420        |
| VIBRATION LEVEL<br>3 AXES (ISO 20643)<br>BREAKING / DRILLING (m/s <sup>2</sup> ) | 20.2 / 21.2 | 20.2 / 21.2 | 20.2 / 21.2 |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC)                                     | 103         |             |             |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)                                       | 88          |             |             |
| CHUCK SIZE (mm)                                                                  | Rd 19 x 95  | Rd 19 x 95  | Rd 19 x 95  |
| PART NUMBER                                                                      | T022083     | Z0027413    | T022322     |

\*Not sold within EU / EEA



| MODEL                                                                            | CP 0009 E*               | CP 0009 ES               | CP 0009 F*  |
|----------------------------------------------------------------------------------|--------------------------|--------------------------|-------------|
| WEIGHT (kg)                                                                      | 4                        | 4.5                      | 4           |
| LENGTH (mm)                                                                      | 375                      | 375                      | 375         |
| AIR CONSUMPTION (l/s)                                                            | 9                        | 9                        | 9           |
| BLOWS PER MINUTE (bpm)                                                           | 3420                     | 3420                     | 3420        |
| VIBRATION LEVEL<br>3 AXES (ISO 20643)<br>BREAKING / DRILLING (m/s <sup>2</sup> ) | 20.2 / 21.2              | 20.2 / 21.2              | 20.2 / 21.2 |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC)                                     | 103                      |                          |             |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)                                       | 88                       |                          |             |
| CHUCK SIZE (mm)                                                                  | Rd 19 x 14.7<br>Hex x 89 | Rd 19 x 14.7<br>Hex x 89 | Spline      |
| PART NUMBER                                                                      | T022180                  | T022330                  | T022511     |

\*Not sold within EU / EEA



| MODEL                                                                            | CP 0014 RR* | CP 0014 RRBS |
|----------------------------------------------------------------------------------|-------------|--------------|
| WEIGHT (kg)                                                                      | 6.5         | 7            |
| LENGTH (mm)                                                                      | 470         | 470          |
| AIR CONSUMPTION (l/s)                                                            | 22          | 22           |
| BLOWS PER MINUTE (bpm)                                                           | 2520        | 2520         |
| VIBRATION LEVEL<br>3 AXES (ISO 20643)<br>BREAKING / DRILLING (m/s <sup>2</sup> ) | 35.4 / 45.3 | 35.4 / 45.3  |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC)                                     |             |              |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)                                       |             |              |
| CHUCK SIZE (mm)                                                                  | Hex 22 x 82 | Hex 22 x 82  |
| PART NUMBER                                                                      | T022173     | T022321      |

\*Not sold within EU / EEA

## Sinkers / Surface Rock Drills



| MODEL                                                  | CP 0022       | CP 0022      | CP 0032       |
|--------------------------------------------------------|---------------|--------------|---------------|
| WEIGHT (kg)                                            | 15            | 15           | 24.5          |
| LENGTH (mm)                                            | 475           | 500          | 560           |
| AIR CONSUMPTION (l/s)                                  | 22            | 22           | 48            |
| BLOWS PER MINUTE (bpm)                                 | 2220          | 2220         | 2100          |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 25.7          | 25.7         | 21.9          |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 116           | 116          | 122           |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 106           | 106          | 111           |
| CHUCK SIZE (mm)                                        | Hex 22 x 82.5 | Hex 22 x 108 | Hex 22 x 82.5 |
| PART NUMBER                                            | 8900 0020 01  | 8900 0020 02 | T022318       |



| MODEL                                                  | CP 0032 S    | CP 0032      | CP 0032      |
|--------------------------------------------------------|--------------|--------------|--------------|
| WEIGHT (kg)                                            | 28           | 26           | 26           |
| LENGTH (mm)                                            | 575          | 575          | 575          |
| AIR CONSUMPTION (l/s)                                  | 48           | 48           | 48           |
| BLOWS PER MINUTE (bpm)                                 | 2100         | 2100         | 2100         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 21.9         | 21.9         | 21.9         |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 114          | 122          | 122          |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 103          | 111          | 111          |
| CHUCK SIZE (mm)                                        | Hex 22 x 108 | Hex 22 x 108 | Hex 25 x 108 |
| PART NUMBER                                            | T025431      | T022117      | T022319      |



| MODEL                                                  | CP 0069 WET  | CP 0069      | CP 0069      |
|--------------------------------------------------------|--------------|--------------|--------------|
| WEIGHT (kg)                                            | 27.5         | 27.5         | 27.5         |
| LENGTH (mm)                                            | 610          | 610          | 610          |
| AIR CONSUMPTION (l/s)                                  | 61           | 61           | 61           |
| BLOWS PER MINUTE (bpm)                                 | 1920         | 1920         | 1920         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 29           | 29           | 29           |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 124          | 124          | 124          |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 113          | 113          | 113          |
| CHUCK SIZE (mm)                                        | Hex 22 x 108 | Hex 25 x 108 | Hex 22 x 108 |
| PART NUMBER                                            | T025423      | T022259      | T006661      |

## Core Drill



|                                                        |            |
|--------------------------------------------------------|------------|
| MODEL                                                  | CP 0315    |
| POWER (kW)                                             | 0.9        |
| WEIGHT (kg)                                            | 6          |
| AIR CONSUMPTION (L/S)                                  | 20         |
| REVOLUTIONS (rpm)                                      | 750        |
| DRILLING DIAMETER (mm)                                 | 50-150     |
| OUTPUT SHAFT THREAD (mm)                               | 45 / 64-16 |
| AIR INLET (in)                                         | 1/2" BSP   |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 7.4        |
| PART NUMBER                                            | T024733    |

## Scabblers



|                                                        |           |              |          |
|--------------------------------------------------------|-----------|--------------|----------|
| MODEL                                                  | CP 0006   | CP 0006 SVR  | CP 0066  |
| WEIGHT (kg)                                            | 5         | 6.5          | 4.5      |
| LENGTH (mm)                                            | 470       | 510          | 280      |
| AIR CONSUMPTION (l/s)                                  | 13        | 13           | 11.5     |
| BLOWS PER MINUTE (bpm)                                 | 3000      | 3000         | 3000     |
| AIR INLET                                              | 1/2" NPTF | 1/2" NPTF    | 1/2" BSP |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 23.1      | 7.1          | 12.8     |
| SOUND PRESSURE LEVEL<br>(2000/14/EC) dB(A)             | 92        | 92           |          |
| PART NUMBER                                            | T022137   | 8900 0040 01 | T024412  |

## Saw



| MODEL                                                  | CP 0044* |
|--------------------------------------------------------|----------|
| POWER (kW)                                             | 3        |
| WEIGHT (kg)                                            | 11       |
| AIR CONSUMPTION (l/s)                                  | 40       |
| REVOLUTIONS (rpm)                                      | 4800     |
| BLADE (mm)                                             | 355      |
| MAX DEPTH (mm)                                         | 100      |
| ARBOR (mm)                                             | 25       |
| AIR INLET                                              | 1/2" NPT |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 6.6      |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) dB(A)     | 112      |
| PART NUMBER                                            | T024421  |

\*Not sold within EU / EEA

## Pumps



| MODEL                 | CP 0010  | CP 0020 | CP 0077  |
|-----------------------|----------|---------|----------|
| POWER (kW)            | 2.2      | 2.9     |          |
| WEIGHT (kg)           | 15       | 26      | 69       |
| MIN. OPENING (mm)     | 210x230  | 230x240 |          |
| MAX SUCTION LIFT (m)  |          |         | 6.1      |
| MAX HEAD (m)          | 30.5     | 27.4    | 53       |
| AIR CONSUMPTION (l/s) | 47       | 51      | 40       |
| AIR INLET (in)        | 3/4" NPT | 1" NPT  | 3/4" NPT |
| DISCHARGE (in)        | 2" NPT   | 2½" NPT | 2½" NPT  |
| PART NUMBER           | T022224  | T022185 | T024005  |

**Notes:**





**Hydraulic Equipment**

## Power Packs



| MODEL                   | PAC P9               | PAC P13               | PAC P18                      |
|-------------------------|----------------------|-----------------------|------------------------------|
| ENGINE                  | 9 HP<br>Honda Petrol | 13 HP<br>Honda Petrol | 18 HP B&S<br>Vanguard Petrol |
| WEIGHT (INCL OIL) (kg)  | 59                   | 87                    | 110                          |
| DIMENSIONS (LxWxH) (mm) | 585 x 525 x 680      | 705 x 600 x 745       | 720 x 700 x 745              |
| OIL FLOW (l/min)        | 20                   | 20-30                 | 20-40                        |
| MAXIMUM PRESSURE (bar)  | 150                  | 150                   | 150                          |
| FUEL CAPACITY (l)       | 6                    | 6.5                   | 7.2                          |
| EHTMA CLASS             | C                    | C/D                   | C/D/E                        |
| HOSE INCLUDED           | NO                   | NO                    | NO                           |
| POWER ON DEMAND (POD)   | YES                  | YES                   | NO                           |
| OIL CONTROL: ENGINE OIL | YES                  | YES                   | YES                          |
| ELECTRIC START          | NO                   | NO                    | YES                          |
| PART NUMBER             | 1807 0080 33         | 1807 0110 29          | 1807 0160 28                 |
| NON-SILENCED VERSIONS * | 1807 0080 26         | 1807 0110 25          | 1807 0160 34                 |

\* Not sold within EU / EEA



| MODEL                   | PAC D10                    |
|-------------------------|----------------------------|
| ENGINE                  | 18 HP<br>Lombardini Diesel |
| WEIGHT (INCL OIL) (kg)  | 116                        |
| DIMENSIONS (LxWxH) (mm) | 705 x 600 x 745            |
| OIL FLOW (l/min)        | 20                         |
| MAXIMUM PRESSURE (bar)  | 140                        |
| FUEL CAPACITY (l)       | 5                          |
| EHTMA CLASS             | C                          |
| HOSE INCLUDED           | NO                         |
| POWER ON DEMAND (POD)   | NO                         |
| OIL CONTROL: ENGINE OIL | NO                         |
| ELECTRIC START          | YES                        |
| PART NUMBER             | -                          |
| NON-SILENCED VERSIONS*  | 1807 0110 27               |

\* Not sold within EU / EEA

## Pick Hammer



| MODEL                                                               | BRK 25 D     |
|---------------------------------------------------------------------|--------------|
| SHANK SIZE (hex mm)                                                 | 22x82,5      |
| WEIGHT (kg)                                                         | 12,6         |
| LENGTH (mm)                                                         | 600          |
| OIL FLOW (l/min)                                                    | 20           |
| WORKING PRESSURE (bar)                                              | 70-90        |
| MAX. RETURN LINE PRESSURE (bar)                                     | 10           |
| BLOWS PER MINUTE (bpm)                                              | 2400         |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup>              | 16,5         |
| SOUND POWER LEVEL GUARANTEED<br>(2000/14/EC) L <sub>w</sub> , dB(A) | 105          |
| SOUND PRESSURE LEVEL<br>(ISO 11203) L <sub>p</sub> , r=1m           | 93           |
| EHTMA CLASS                                                         | C            |
| PART NUMBER                                                         | 1801 1746 12 |

# Breakers



| MODEL                                                 | BRK 40       | BRK 40 VR    |
|-------------------------------------------------------|--------------|--------------|
| WEIGHT (kg)                                           | 17.5-19      | 22-23.5      |
| LENGTH (mm)                                           | 640-690      | 650-700      |
| OIL FLOW (l/min)                                      | 20           | 20           |
| WORKING PRESSURE (bar)                                | 95-115       | 95-115       |
| MAX. RETURN LINE PRESSURE (bar)                       | 10           | 10           |
| BLOWS PER MINUTE (bpm)                                | 1600         | 1600         |
| VIBRATION LEVEL 3 AXES (ISO 20643) m/s <sup>2</sup> * | 15.1         | 5.0          |
| SOUND POWER LEVEL (2000/14/EC) Lw dB(A) *             | 107          | 107          |
| SOUND PRESSURE LEVEL (2000/14/EC) Lp dB(A) *          | 93           | 93           |
| EHTMA CLASS                                           | C            | C            |
| PART NUMBER                                           |              |              |
| 25 x 108 mm (1 x 4¼ in)                               | 1801 3446 11 | 1801 3447 19 |
| 28 x 152 mm (1⅞ x 6 in)                               | -            | 1801 3447 20 |
| 28 x 160 mm (1⅞ x 6¼ in)                              | 1801 3446 58 | -            |
| 32 x 152 mm (1¼ x 6 in)                               | 1801 3446 60 | 1801 3447 21 |
| 32 x 160 mm (1¼ x 6¼ in)                              | 1801 3446 62 | 1801 3447 22 |
| HIGH BACK PRESSURE VERSION                            |              |              |
| MAX. RETURN LINE PRESSURE (bar)                       | -            | -            |
| PART NUMBER                                           |              |              |
| 28 x 152 mm (1⅞ x 6 in)                               | -            | -            |
| 32 x 152 mm (1¼ x 6 in)                               | -            | -            |

\* BRK 40 measured at 20 l/min



| MODEL                                                     | BRK 55       | BRK 55 VR    |
|-----------------------------------------------------------|--------------|--------------|
| WEIGHT (kg)                                               | 20.5-22      | 25-26.5      |
| LENGTH (mm)                                               | 680-730      | 690-735      |
| OIL FLOW (l/min)                                          | 30 *         | 30 *         |
| WORKING PRESSURE (bar)                                    | 110-125      | 110-125      |
| MAX. RETURN LINE PRESSURE (bar)                           | 15           | 15           |
| BLOWS PER MINUTE at flow range (bpm)                      | 1500-1980    | 1500-1980    |
| VIBRATION LEVEL 3 AXES (ISO 20643) m/s <sup>2</sup> **    | 16.6         | 4.6          |
| SOUND POWER LEVEL (2000/14/EC) L <sub>w</sub> dB(A) **    | 107          | 107          |
| SOUND PRESSURE LEVEL (2000/14/EC) L <sub>p</sub> dB(A) ** | 94           | 94           |
| EHTMA CLASS                                               | D (C) *      | D (C) *      |
| PART NUMBER                                               |              |              |
| 25 x 108 mm (1 x 4¼ in)                                   | 1801 3546 05 | 1801 3547 23 |
| 28 x 152 mm (1⅞ x 6 in)                                   | -            | -            |
| 28 x 160 mm (1⅞ x 6¼ in)                                  | 1801 3546 63 | -            |
| 32 x 152 mm (1¼ x 6 in)                                   | 1801 3546 65 | 1801 3547 24 |
| 32 x 160 mm (1¼ x 6¼ in)                                  | 1801 3546 68 | 1801 3547 25 |
| HIGH BACK PRESSURE VERSION                                |              |              |
| MAX. RETURN LINE PRESSURE (bar)                           | 30           | 30           |
| PART NUMBER                                               |              |              |
| 28 x 152 mm (1⅞ x 6 in)                                   | 1801 3546 83 | -            |
| 32 x 152 mm (1¼ x 6 in)                                   | -            | 1801 3546 66 |

\* Can be adjusted to 20 l/min

\*\* BRK 55 measured at 20 l/min

# Breakers



| MODEL                                                     | BRK 70       | BRK 70 VR    |
|-----------------------------------------------------------|--------------|--------------|
| WEIGHT (kg)                                               | 25           | 29.5         |
| LENGTH (mm)                                               | 760          | 765          |
| OIL FLOW (l/min)                                          | 30 *         | 30 *         |
| WORKING PRESSURE (bar)                                    | 110-125      | 110-125      |
| MAX. RETURN LINE PRESSURE (bar)                           | 15           | 15           |
| BLOWS PER MINUTE at flow range (bpm)                      | 1380-1860    | 1380-1860    |
| VIBRATION LEVEL 3 AXES (ISO 20643) m/s <sup>2</sup> **    | 19.4         | 4.6          |
| SOUND POWER LEVEL (2000/14/EC) L <sub>w</sub> dB(A) **    | 110          | 110          |
| SOUND PRESSURE LEVEL (2000/14/EC) L <sub>p</sub> dB(A) ** | 95           | 95           |
| EHTMA CLASS                                               | D (C) *      | D (C) *      |
| PART NUMBER                                               |              |              |
| 25 x 108 mm (1 x 4¼ in)                                   | -            | -            |
| 28 x 152 mm (1⅞ x 6 in)                                   | -            | -            |
| 28 x 160 mm (1⅞ x 6¼ in)                                  | 1801 3646 70 | 1801 3647 26 |
| 32 x 152 mm (1¼ x 6 in)                                   | 1801 3646 73 | 1801 3647 27 |
| 32 x 160 mm (1¼ x 6¼ in)                                  | 1801 3646 07 | 1801 3647 28 |
| HIGH BACK PRESSURE VERSION                                |              |              |
| MAX. RETURN LINE PRESSURE (bar)                           | 30           | 30           |
| PART NUMBER                                               |              |              |
| 28 x 152 mm (1⅞ x 6 in)                                   | 1801 3646 84 | -            |
| 32 x 152 mm (1¼ x 6 in)                                   | -            | 1801 3646 71 |

\* Can be adjusted to 20 l/min  
 \*\* BRK 70 measured at 20 l/min



| MODEL                                                     | BRK 95       | BRK 95 VR    |
|-----------------------------------------------------------|--------------|--------------|
| WEIGHT (kg)                                               | 31.5         | 36           |
| LENGTH (mm)                                               | 760          | 765          |
| OIL FLOW (l/min)                                          | 30 *         | 30 *         |
| WORKING PRESSURE (bar)                                    | 110-125      | 110-125      |
| MAX. RETURN LINE PRESSURE (bar)                           | 15           | 15           |
| BLOWS PER MINUTE at flow range (bpm)                      | 1100-1350    | 1100-1350    |
| VIBRATION LEVEL 3 AXES (ISO 20643) m/s <sup>2</sup> **    | 20.1         | 5.4          |
| SOUND POWER LEVEL (2000/14/EC) L <sub>w</sub> dB(A) **    | 106          | 106          |
| SOUND PRESSURE LEVEL (2000/14/EC) L <sub>p</sub> dB(A) ** | 93           | 93           |
| EHTMA CLASS                                               | D (E) **     | D (E) **     |
| PART NUMBER                                               |              |              |
| 25 x 108 mm (1 x 4¼ in)                                   | -            | -            |
| 28 x 152 mm (1½ x 6 in)                                   | -            | -            |
| 28 x 160 mm (1½ x 6¼ in)                                  | -            | -            |
| 32 x 152 mm (1¼ x 6 in)                                   | 1801 3746 75 | 1801 3747 29 |
| 32 x 160 mm (1¼ x 6¼ in)                                  | 1801 3746 09 | 1801 3747 30 |
| HIGH BACK PRESSURE VERSION                                |              |              |
| MAX. RETURN LINE PRESSURE (bar)                           | 30           | -            |
| PART NUMBER                                               |              |              |
| 28 x 152 mm (1½ x 6 in)                                   | 1801 3746 85 | -            |
| 32 x 152 mm (1¼ x 6 in)                                   | -            | -            |

\* Can be adjusted to 40 l/min

\*\* BRK 95 measured at 30 l/min

# Cut-Off Saws



| MODEL                                                  | SAW 14       | SAW 16       |
|--------------------------------------------------------|--------------|--------------|
| WEIGHT (kg)                                            | 9.8          | 10.6         |
| OIL FLOW (l/min)                                       | 20-30        | 20-40        |
| MAXIMUM OIL PRESSURE (bar)                             | 170          | 170          |
| REVOLUTIONS (rpm)                                      | 2500-4000    | 2000-4000    |
| SPEED (m/s)                                            | 46-75        | 42-85        |
| DISC SIZE (mm)                                         | 355          | 405          |
| ARBOR SIZE (mm)                                        | 25.4         | 25.4         |
| CUTTING DEPTH (mm)                                     | 133          | 160          |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 4,9          | 4,9          |
| SOUND POWER LEVEL GUARANTEED<br>(2000/14/EC) Lw, dB(A) | 99           | 115          |
| SOUND PRESSURE LEVEL<br>(ISO 11203) Lp, dB(A) r=1m     | 86           | 102          |
| EHTMA CLASS                                            | C/D          | C/D/E        |
| PART NUMBER                                            | 1809 0140 03 | 1809 0166 13 |

# Core Drills



| MODEL                                                  | COR 5        | COR 15       |
|--------------------------------------------------------|--------------|--------------|
| WEIGHT (kg)                                            | 8.2          | 8.2          |
| OIL FLOW (l/min)                                       | 20-30        | 20-30        |
| LENGTH WITHOUT DRILL (mm)                              | 414          | 406          |
| WORKING PRESSURE (bar)                                 | 80-172       | 80-172       |
| REVOLUTIONS (rpm)                                      | 600-900      | 1500-2250    |
| DRILL DIAMETER (mm)                                    | 50-202       | 12-75        |
| THREAD FEMALE (drive) *                                | ½" BSP       | ½" BSP       |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) m/s <sup>2</sup> | 3,1          | 2,7          |
| SOUND PRESSURE LEVEL<br>(ISO 11203) Lp, dB(A) r=1m     | <70          | <70          |
| EHTMA CLASS                                            | C/D          | C/D          |
| PART NUMBER                                            | 1806 1014 54 | 1806 1014 55 |

\* 1/2" BSP male x 1 1/4 UNC male drive adaptor included for use of larger diameter core bits.

# Pumps



| MODEL                          | WAP 2        | WAP 3        |
|--------------------------------|--------------|--------------|
| WEIGHT (kg)                    | 10.25        | 12.70        |
| DIMENSIONS HxW (mm)            | 267 x 215    | 360 x 300    |
| OIL FLOW (l/min)               | 18-24        | 26-38        |
| WORKING PRESSURE (bar)         | 100          | 140          |
| MAXIMUM WORKING PRESSURE (bar) | 160          | 172          |
| PUMP MAXIMUM HEAD (m)          | 25           | 32           |
| PUMP MAXIMUM FLOW (l/min)      | 840          | 1920         |
| DISCHARGE                      | 2"           | 3"           |
| SOLIDS HANDLING UP TO (mm)     | 10           | 60           |
| EHTMA CLASS                    | C            | D            |
| PART NUMBER                    | 1806 1014 41 | 1806 1014 42 |

**Notes:**





**Petrol-driven Equipment**

# Breaker



| MODEL                                                                | RED HAWK     |
|----------------------------------------------------------------------|--------------|
| WEIGHT (kg)                                                          | 22.5         |
| LENGTH (mm)                                                          | 694          |
| IMPACT ENERGY (joules)                                               | 24           |
| IMPACT RATE (bpm)                                                    | 2600         |
| ENGINE POWER (kW)                                                    | 2            |
| FUEL CAPACITY (l)                                                    | 1.2          |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) (m/s <sup>2</sup> )            | 8.4          |
| SOUND POWER LEVEL<br>GUARANTEED (2000/14/EC) (L <sub>w</sub> ) dB(A) | 107          |
| SOUND PRESSURE LEVEL<br>(ISO 11203) dB(A)                            | 94           |
| SHANK SIZE (mm)                                                      | 22x108       |
| PART NUMBER                                                          | 8318 0900 02 |



## **Compaction Equipment**

# Forward Soil and Asphalt Plates



| MODEL                                                        | MV 52        | MV 58        | MV 84        |
|--------------------------------------------------------------|--------------|--------------|--------------|
| OPERATING WEIGHT (kg)                                        | 51.4         | 56.4         | 85.1         |
| CENTRIFUGAL FORCE (kN)                                       | 7.5          | 9.5          | 16.5         |
| SPEED (m/min)                                                | 24           | 25           | 34           |
| PLATE WIDTH (mm)                                             | 320          | 350          | 420          |
| ENGINE                                                       | Honda        | Honda        | Honda        |
| SOUND POWER GUARANTEED (LwAdB(A))                            | 100          | 100          | 103          |
| SOUND PRESSURE AT OPERATORS EAR (LwAdB(A))                   | 89           | 88           | 91           |
| H/A VIBRATIONS (m/s <sup>2</sup> )                           | 6.9          | 7.9          | 6.7          |
| H/A VIBRATIONS, VIBRATION REDUCED HANDLE (m/s <sup>2</sup> ) | 1.8          | 1.9          | 1.2          |
| PART NUMBER                                                  | 4812 0991 25 | 4812 0991 26 | 4812 0991 27 |



| MODEL                                                        | MV 135       | MV 140       |
|--------------------------------------------------------------|--------------|--------------|
| OPERATING WEIGHT (kg)                                        | 130.9        | 136.9        |
| CENTRIFUGAL FORCE (kN)                                       | 19.4         | 19.4         |
| SPEED (m/min)                                                | 22           | 22           |
| PLATE WIDTH (mm)                                             | 500          | 500          |
| ENGINE                                                       | Honda        | Hatz         |
| SOUND POWER GUARANTEED (LwAdB(A))                            | 102          | 104          |
| SOUND PRESSURE AT OPERATORS EAR (LwAdB(A))                   | 91           | 93           |
| H/A VIBRATIONS (m/s <sup>2</sup> )                           | 5.4          | 6.8          |
| H/A VIBRATIONS, VIBRATION REDUCED HANDLE (m/s <sup>2</sup> ) | 1.1          | 1.1          |
| PART NUMBER                                                  | 4812 0991 30 | 4812 0991 31 |



| MODEL                                                        | MV 90        | MV 100       | MV 115       |
|--------------------------------------------------------------|--------------|--------------|--------------|
| OPERATING WEIGHT (kg)                                        | 87           | 97.6         | 114.1        |
| CENTRIFUGAL FORCE (kN)                                       | 11.6         | 15.5         | 14.5         |
| SPEED (m/min)                                                | 27           | 25           | 25           |
| PLATE WIDTH (mm)                                             | 420          | 500          | 500          |
| ENGINE                                                       | Honda        | Honda        | Hatz         |
| SOUND POWER GUARANTEED (L <sub>w</sub> AdB(A))               | 104          | 104          | 104          |
| SOUND PRESSURE AT OPERATORS EAR (L <sub>w</sub> AdB(A))      | 93           | 93           | 93           |
| H/A VIBRATIONS (m/s <sup>2</sup> )                           | 6            | 6            | 9.3          |
| H/A VIBRATIONS, VIBRATION REDUCED HANDLE (m/s <sup>2</sup> ) | 1.2          | 1.3          | 1.9          |
| PART NUMBER                                                  | 4812 0991 32 | 4812 0991 28 | 4812 0991 29 |

# Walk Behind Double Drum Roller



| MODEL                                      | MR 7000<br>Electric Start | MR 7000<br>Manual Start |
|--------------------------------------------|---------------------------|-------------------------|
| OPERATING WEIGHT (kg)                      | 658                       | 658                     |
| CENTRIFUGAL FORCE (kN)                     | 21                        | 21                      |
| SPEED (m/min)                              | 60/38                     | 60/38                   |
| PLATE WIDTH (mm)                           | 650                       | 650                     |
| ENGINE                                     | Hatz                      | Hatz                    |
| SOUND POWER GUARANTEED (LwAdB(A))          | 107                       | 107                     |
| SOUND PRESSURE AT OPERATORS EAR (LwAdB(A)) | 90                        | 90                      |
| H/A VIBRATIONS (m/s²)                      | 4                         | 4.3                     |
| PART NUMBER                                | 4812 0991 46              | 4812 0991 47            |

# Forward and Reversible Plates



| MODEL                                      | MV 165       | MV 170       |
|--------------------------------------------|--------------|--------------|
| OPERATING WEIGHT (kg)                      | 156          | 171          |
| CENTRIFUGAL FORCE (kN)                     | 28           | 28           |
| SPEED (m/min)                              | 22           | 22           |
| PLATE WIDTH (mm)                           | 450          | 450          |
| ENGINE                                     | Honda        | Hatz         |
| SOUND POWER GUARANTEED (LwAdB(A))          | 108          | 108          |
| SOUND PRESSURE AT OPERATORS EAR (LwAdB(A)) | 92           | 92           |
| H/A VIBRATIONS (m/s²)                      | 1.5          | 2.4          |
| PART NUMBER                                | 4812 0991 42 | 4812 0991 43 |



| MODEL                                                   | MV 220       | MV 245<br>Electric Start |
|---------------------------------------------------------|--------------|--------------------------|
| OPERATING WEIGHT (kg)                                   | 215          | 245                      |
| CENTRIFUGAL FORCE (kN)                                  | 36           | 36                       |
| SPEED (m/min)                                           | 25           | 25                       |
| PLATE WIDTH (mm)                                        | 500          | 500                      |
| ENGINE                                                  | Honda        | Hatz                     |
| SOUND POWER GUARANTEED (L <sub>w</sub> AdB(A))          | 105          | 108                      |
| SOUND PRESSURE AT OPERATORS EAR (L <sub>w</sub> AdB(A)) | 90           | 90                       |
| H/A VIBRATIONS (m/s <sup>2</sup> )                      | 3.5          | 3.5                      |
| PART NUMBER                                             | 4812 0991 44 | 4812 0991 45             |



| MODEL                                                   | MV 305       | MV 320       |
|---------------------------------------------------------|--------------|--------------|
| OPERATING WEIGHT (kg)                                   | 263          | 300          |
| CENTRIFUGAL FORCE (kN)                                  | 40           | 40           |
| SPEED (m/min)                                           | 25           | 25           |
| PLATE WIDTH (mm)                                        | 600          | 600          |
| ENGINE                                                  | Honda        | Hatz         |
| SOUND POWER GUARANTEED (L <sub>w</sub> AdB(A))          | 108          | 108          |
| SOUND PRESSURE AT OPERATORS EAR (L <sub>w</sub> AdB(A)) | 92           | 94           |
| H/A VIBRATIONS (m/s <sup>2</sup> )                      | 2.4          | 1.7          |
| PART NUMBER                                             | 4812 0991 40 | 4812 0991 41 |

## Forward and Reversible Plates



| MODEL                                      | MV 480 Electric Start |
|--------------------------------------------|-----------------------|
| OPERATING WEIGHT (kg)                      | 504                   |
| CENTRIFUGAL FORCE (kN)                     | 60                    |
| SPEED (m/min)                              | 25                    |
| PLATE WIDTH (mm)                           | 700                   |
| ENGINE                                     | Hatz                  |
| SOUND POWER GUARANTEED (LwAdB(A))          | 108                   |
| SOUND PRESSURE AT OPERATORS EAR (LwAdB(A)) | 95                    |
| H/A VIBRATIONS (m/s <sup>2</sup> )         | 2.4                   |
| PART NUMBER                                | 4812 0991 39          |

## Vibrator



| MODEL                                                  | CP 2190   |
|--------------------------------------------------------|-----------|
| WEIGHT (kg)                                            | 19        |
| LENGTH (mm)                                            | 350       |
| DIAMETER (mm)                                          | 64        |
| AIR CONSUMPTION (l/s)                                  | 31        |
| FREQUENCY (vpm)                                        | 12000     |
| AIR INLET (in)                                         | 1/2" NPTF |
| VIBRATION LEVEL 3 AXES (ISO 20643) (m/s <sup>2</sup> ) | 1.6       |
| PART NUMBER                                            | T019308   |

# Tampers



| MODEL                                                     | CP 0003   | CP 0004   |
|-----------------------------------------------------------|-----------|-----------|
| WEIGHT (kg)                                               | 13.5      | 19        |
| LENGTH (mm)                                               | 1320      | 1270      |
| BUTT DIAMETER (mm)                                        | 125       | 160       |
| AIR CONSUMPTION (l/s)                                     | 8.4       | 13        |
| BLOWS PER MINUTE (bpm)                                    | 800       | 780       |
| AIR INLET (in)                                            | 1/2" NPTF | 1/2" NPTF |
| VIBRATION LEVEL 3 AXES<br>(ISO 20643) (m/s <sup>2</sup> ) | 32.3      | 44.8      |
| PART NUMBER                                               | T019307   | T022292   |

# Tampers



| MODEL                                      | MS 620       | MS 680       |
|--------------------------------------------|--------------|--------------|
| OPERATING WEIGHT (kg)                      | 64           | 74           |
| CENTRIFUGAL FORCE (kN)                     | 14.8         | 18.6         |
| SPEED (m/min)                              | 15-18        | 15-18        |
| PLATE WIDTH (mm)                           | 230          | 280          |
| ENGINE                                     | Honda        | Honda        |
| SOUND POWER GUARANTEED (LwAdB(A))          | 104          | 107          |
| SOUND PRESSURE AT OPERATORS EAR (LwAdB(A)) | 91           | 96           |
| H/A VIBRATIONS (m/s <sup>2</sup> )         | 7            | 11.9         |
| PART NUMBER                                | 4812 0991 36 | 4812 0991 37 |



| MODEL                                      | MS 840       |
|--------------------------------------------|--------------|
| OPERATING WEIGHT (kg)                      | 84           |
| CENTRIFUGAL FORCE (kN)                     | 21.4         |
| SPEED (m/min)                              | 13-16        |
| PLATE WIDTH (mm)                           | 280          |
| ENGINE                                     | Hatz         |
| SOUND POWER GUARANTEED (LwAdB(A))          | 106          |
| SOUND PRESSURE AT OPERATORS EAR (LwAdB(A)) | 96           |
| H/A VIBRATIONS (m/s <sup>2</sup> )         | 12.6         |
| PART NUMBER                                | 4812 0991 38 |



**Rig-Mounted Equipment**

## Hydraulic Breakers



| MODEL                                  | <b>RX2</b>          | <b>RX3</b>          |
|----------------------------------------|---------------------|---------------------|
| CARRIER WEIGHT CLASS (t) <sup>1)</sup> | 1,3-3,0             | 2,1-4,5             |
| SERVICE WEIGHT (kg) <sup>2)</sup>      | 117                 | 166                 |
| OIL FLOW RATE (l/min)                  | 15-35               | 30-50               |
| OPERATING PRESSURE (bar)               | 110-130             | 110-140             |
| BLOW FREQUENCY (bpm)                   | 560-1700            | 670-1450            |
| BLOW FREQUENCY (bpm) <sup>3)</sup>     | -                   | -                   |
| WORKING TOOL DIAMETER<br>Ø mm          | 42                  | 52                  |
| WORKING LENGTH OF TOOL (mm)            | 265                 | 320                 |
| SOUND POWER LEVEL GUARANTEED<br>dB(A)  | 109                 | 111                 |
| SOUND PRESSURE LEVEL (r=10m)<br>dB(A)  | 81                  | 83                  |
| PART NUMBER                            | <b>8460 0500 38</b> | <b>8460 0500 39</b> |

| MODEL                                  | <b>RX4</b>          | <b>RX6</b>          |
|----------------------------------------|---------------------|---------------------|
| CARRIER WEIGHT CLASS (t) <sup>1)</sup> | 2,9-6,0             | 4,2-9,0             |
| SERVICE WEIGHT (kg) <sup>2)</sup>      | 233                 | 284                 |
| OIL FLOW RATE (l/min)                  | 35-60               | 45-75               |
| OPERATING PRESSURE (bar)               | 110-140             | 100-140             |
| BLOW FREQUENCY (bpm)                   | 520-1150            | 530-1150            |
| BLOW FREQUENCY (bpm) <sup>3)</sup>     | -                   | -                   |
| WORKING TOOL DIAMETER<br>Ø mm          | 62                  | 70                  |
| WORKING LENGTH OF TOOL (mm)            | 350                 | 380                 |
| SOUND POWER LEVEL GUARANTEED<br>dB(A)  | 113                 | 114                 |
| SOUND PRESSURE LEVEL (r=10m)<br>dB(A)  | 85                  | 86                  |
| PART NUMBER                            | <b>8460 0500 40</b> | <b>8460 0500 41</b> |

1) Weights apply to standard carriers only. Any variances must be agreed with Chicago Pneumatic and/or the carrier manufacturer prior to attachment.

2) Breaker and breaker box with standard adapter plus working tool.

3) Power Control: The blow frequency and impact energy can be adjusted to better meet the application requirements.



| MODEL                                  | <b>RX8</b>          | <b>RX11</b>         |
|----------------------------------------|---------------------|---------------------|
| CARRIER WEIGHT CLASS (t) <sup>1)</sup> | 5,2-12,0            | 9-15                |
| SERVICE WEIGHT (kg) <sup>2)</sup>      | 380                 | 550                 |
| OIL FLOW RATE (l/min)                  | 60-90               | 70-100              |
| OPERATING PRESSURE (bar)               | 120-150             | 120-150             |
| BLOW FREQUENCY (bpm)                   | 530-1050            | 590-1100            |
| BLOW FREQUENCY (bpm) <sup>3)</sup>     | -                   | -                   |
| WORKING TOOL DIAMETER<br>Ø mm          | 80                  | 80                  |
| WORKING LENGTH OF TOOL (mm)            | 415                 | 390                 |
| SOUND POWER LEVEL GUARANTEED<br>dB(A)  | 115                 | 116                 |
| SOUND PRESSURE LEVEL (r=10m)<br>dB(A)  | 87                  | -                   |
| PART NUMBER                            | <b>8460 0500 42</b> | <b>3363 1095 21</b> |

| MODEL                                  | <b>RX14</b>         | <b>RX18</b>         |
|----------------------------------------|---------------------|---------------------|
| CARRIER WEIGHT CLASS (t) <sup>1)</sup> | 10-17               | 15-24               |
| SERVICE WEIGHT (kg) <sup>2)</sup>      | 800                 | 1200                |
| OIL FLOW RATE (l/min)                  | 100-120             | 120-140             |
| OPERATING PRESSURE (bar)               | 150-170             | 150-170             |
| BLOW FREQUENCY (bpm)                   | 650-850             | 550-720             |
| BLOW FREQUENCY (bpm) <sup>3)</sup>     | -                   | -                   |
| WORKING TOOL DIAMETER<br>Ø mm          | 100                 | 120                 |
| WORKING LENGTH OF TOOL (mm)            | 495                 | 540                 |
| SOUND POWER LEVEL GUARANTEED<br>dB(A)  | -                   | -                   |
| SOUND PRESSURE LEVEL (r=10m)<br>dB(A)  | -                   | -                   |
| PART NUMBER                            | <b>3363 1049 61</b> | <b>3363 1052 39</b> |

1) Weights apply to standard carriers only. Any variances must be agreed with Chicago Pneumatic and/or the carrier manufacturer prior to attachment.

2) Breaker and breaker box with standard adapter plus working tool.

3) Power Control: The blow frequency and impact energy can be adjusted to better meet the application requirements.

# Hydraulic Breakers



| MODEL                                  | RX22         | RX25         |
|----------------------------------------|--------------|--------------|
| CARRIER WEIGHT CLASS (t) <sup>1)</sup> | 17-28        | 20-33        |
| SERVICE WEIGHT (kg) <sup>2)</sup>      | 1500         | 1800         |
| OIL FLOW RATE (l/min)                  | 140-160      | 130-180      |
| OPERATING PRESSURE (bar)               | 150-170      | 150-170      |
| BLOW FREQUENCY (bpm)                   | 520-680      | 400-680      |
| BLOW FREQUENCY (bpm) <sup>3)</sup>     | -            | 460-800      |
| WORKING TOOL DIAMETER<br>Ø mm          | 135          | 140          |
| WORKING LENGTH OF TOOL (mm)            | 565          | 585          |
| SOUND POWER LEVEL GUARANTEED<br>dB(A)  | -            | -            |
| SOUND PRESSURE LEVEL<br>(r=10m) dB(A)  | -            | -            |
| PART NUMBER                            | 3363 1051 01 | 3363 1056 01 |

| MODEL                                  | RX29         | RX45         |
|----------------------------------------|--------------|--------------|
| CARRIER WEIGHT CLASS (t) <sup>1)</sup> | 25-40        | 29-46        |
| SERVICE WEIGHT (kg) <sup>2)</sup>      | 2200         | 3000         |
| OIL FLOW RATE (l/min)                  | 150-200      | 210-260      |
| OPERATING PRESSURE (bar)               | 150-170      | 160-180      |
| BLOW FREQUENCY (bpm)                   | 375-600      | 380-580      |
| BLOW FREQUENCY (bpm) <sup>3)</sup>     | 440-800      | -            |
| WORKING TOOL DIAMETER<br>Ø mm          | 150          | 165          |
| WORKING LENGTH OF TOOL (mm)            | 590          | 670          |
| SOUND POWER LEVEL GUARANTEED<br>dB(A)  | -            | 121          |
| SOUND PRESSURE LEVEL<br>(r=10m) dB(A)  | -            | -            |
| PART NUMBER                            | 3363 1058 93 | 3363 1053 59 |

1) Weights apply to standard carriers only. Any variances must be agreed with Chicago Pneumatic and/or the carrier manufacturer prior to attachment.

2) Breaker and breaker box with standard adapter plus working tool.

3) Power Control: The blow frequency and impact energy can be adjusted to better meet the application requirements.



| MODEL                                  | <b>RX53</b>         |
|----------------------------------------|---------------------|
| CARRIER WEIGHT CLASS (t) <sup>1)</sup> | 40-70               |
| SERVICE WEIGHT (kg) <sup>2)</sup>      | 4200                |
| OIL FLOW RATE (l/min)                  | 250-320             |
| OPERATING PRESSURE (bar)               | 160-180             |
| BLOW FREQUENCY (bpm)                   | 350-560             |
| BLOW FREQUENCY (bpm) <sup>3)</sup>     | -                   |
| WORKING TOOL DIAMETER<br>Ø mm          | 180                 |
| WORKING LENGTH OF TOOL (mm)            | 735                 |
| SOUND POWER LEVEL GUARANTEED<br>dB(A)  | -                   |
| SOUND PRESSURE LEVEL<br>(r=10m) dB(A)  | -                   |
| PART NUMBER                            | <b>3363 1097 39</b> |

1) Weights apply to standard carriers only. Any variances must be agreed with Chicago Pneumatic and/or the carrier manufacturer prior to attachment.

2) Breaker and breaker box with standard adapter plus working tool.

3) Power Control: The blow frequency and impact energy can be adjusted to better meet the application requirements.

Notes:





**Compressors**

# Portable Compressors



| MODEL                                                  | CPS 2.0<br>CPS 70 | CPS 2.5<br>CPS 90 | CPS 3.0<br>CPS 110 |
|--------------------------------------------------------|-------------------|-------------------|--------------------|
| AIRFLOW ACC. TO ISO 1217 AT<br>WORKING PRESSURE m³/min | 2.0               | 2.5               | 3.0                |
| WORKING PRESSURE bar(e) psi                            | 7 / 102           | 7 / 102           | 7 / 102            |
| AIR FLOW (l/s)                                         | 33,3              | 41,7              | 50                 |
| MIN./MAX. WORKING SPEED (rpm)                          | 2400-3600         | 2400-3000         | 1850-2750          |
| SOUND POWER LEVEL ACC<br>to 20001/14EC dB(A)           | <98               | <98               | <98                |
| CAPACITY OF FUEL TANK (l)                              | 32                | 32                | 40                 |
| AIR OUTLET VALVES - QTY X SIZE (in)                    | 2 x 3/4           | 2 x 3/4           | 2 x 3/4            |
| LENGTH WITH HORIZONTAL<br>TOWBAR (mm)                  | 2953              | 2953              | 3863               |
| WIDTH (mm)                                             | 1280              | 1280              | 1310               |
| HEIGHT (mm)                                            | 1205              | 1205              | 1282               |
| OPERATIONAL WEIGHT<br>(FULL FUEL TANK) (kg)            | 552               | 556               | 730                |
| ENGINE                                                 | Kubota            | Kubota            | Deutz              |
| ENGINE TYPE                                            | D905              | D1105             | D2011L02           |
| OUTPUT AT NOMINAL SPEED (kW)                           | 18.5              | 19.4              | 23.3               |



| MODEL                                                               | CPS 3.5<br>CPS 130 | CPS 4.5<br>CPS 150 | CPS 5.5<br>CPS 185 |
|---------------------------------------------------------------------|--------------------|--------------------|--------------------|
| AIRFLOW ACC. TO ISO 1217 AT<br>WORKING PRESSURE m <sup>3</sup> /min | 3.7                | 4.3                | 5.3                |
| WORKING PRESSURE bar(e) psi                                         | 7 / 102            | 7 / 102            | 7 / 102            |
| AIR FLOW (l/s)                                                      | 61,7               | 71,7               | 88,3               |
| MIN./MAX. WORKING SPEED (rpm)                                       | 1850-2400          | 1850-2300          | 1850-2750          |
| SOUND POWER LEVEL ACC<br>to 20001/14EC dB(A)                        | <98                | <98                | <98                |
| CAPACITY OF FUEL TANK (l)                                           | 80                 | 80                 | 80                 |
| AIR OUTLET VALVES - QTY X SIZE (in)                                 | 2 x 3/4            | 2 x 3/4            | 3 x 3/4            |
| LENGTH WITH HORIZONTAL<br>TOWBAR (mm)                               | 3758               | 3758               | 3758               |
| WIDTH (mm)                                                          | 1400               | 1400               | 1400               |
| HEIGHT (mm)                                                         | 1280               | 1280               | 1280               |
| OPERATIONAL WEIGHT<br>(FULL FUEL TANK) (kg)                         | 918                | 960                | 960                |
| ENGINE                                                              | Deutz              | Deutz              | Deutz              |
| ENGINE TYPE                                                         | D2011L03           | D2011L03           | D2011L03           |
| OUTPUT AT NOMINAL SPEED (kW)                                        | 32.5               | 31.5               | 36.0               |

## Portable Compressors



| MODEL                                                  | CPS 7.5<br>CPS 275     | CPS 11.0<br>CPS 375    | CPS 11-12<br>CPS 375-12 |
|--------------------------------------------------------|------------------------|------------------------|-------------------------|
| AIRFLOW ACC. TO ISO 1217 AT<br>WORKING PRESSURE m³/min | 7.6                    | 11.1                   | 10.4                    |
| WORKING PRESSURE bar(e) psi                            | 7 / 102                | 7 / 102                | 12 / 175                |
| AIR FLOW (l/s)                                         | 126,7                  | 185                    | 173,3                   |
| MIN./MAX. WORKING SPEED (rpm)                          | 1800-2400              | 1700-2300              | 1550-2200               |
| SOUND POWER LEVEL ACC<br>to 20001/14EC dB(A)           | <99                    | <99                    | <99                     |
| CAPACITY OF FUEL TANK (l)                              | 117                    | 175                    | 175                     |
| AIR OUTLET VALVES - QTY X SIZE (in)                    | 3 x 3/4<br>+ 1 x 1 1/2 | 3 x 3/4<br>+ 1 x 1 1/2 | 3 x 3/4<br>+ 1 x 1 1/2  |
| LENGTH WITH HORIZONTAL<br>TOWBAR (mm)                  | 4365                   | 4546                   | 4546                    |
| WIDTH (mm)                                             | 1680                   | 1770                   | 1770                    |
| HEIGHT (mm)                                            | 1465                   | 1780                   | 1780                    |
| OPERATIONAL WEIGHT<br>(FULL FUEL TANK) (kg)            | 1475                   | 1850                   | 1850                    |
| ENGINE                                                 | Deutz                  | Deutz                  | Deutz                   |
| ENGINE TYPE                                            | BF4M2011               | TCD2012L04             | TCD2013L04              |
| OUTPUT AT NOMINAL SPEED (kW)                           | 58                     | 83.0                   | 104.0                   |



**Generators**

# Portable Generators



| MODEL                                  | CPG 12             | CPG 20             | CPG 30             |
|----------------------------------------|--------------------|--------------------|--------------------|
| PRODUCT CONFIGURATION                  | 400V - 3PH         | 400V - 3PH         | 400V - 3PH         |
| RATED FREQUENCY                        | 50                 | 50                 | 50                 |
| RATED SPEED                            | 1500               | 1500               | 1500               |
| RATED APPARENT POWER (PRP)             | 12                 | 20                 | 30                 |
| RATED VOLTAGE 3PH.<br>LINE TO LINE (A) | 17.3               | 28.9               | 43.3               |
| ENGINE MAKE                            | DEUTZ              | DEUTZ              | DEUTZ              |
| MAKE                                   | F2M 2011 F         | F3M 2011 F         | BF3M 2011 F        |
| RATED NET OUTPUT (kW)                  | 12                 | 19                 | 27.6               |
| BASIC UNIT DIMENSIONS<br>(LxWxH) m     | 2.02 x 1.04 x 1.02 | 2.02 x 1.04 x 1.02 | 2.02 x 1.04 x 1.02 |
| WEIGHT (READY TO OPERATE) (kg)         | 706                | 804                | 827                |

Built and tested to ISO 9001 quality assurance standards.



| MODEL                                  | CPG 40             | CPG 60             |
|----------------------------------------|--------------------|--------------------|
| PRODUCT CONFIGURATION                  | 400V - 3PH         | 400V - 3PH         |
| RATED FREQUENCY                        | 50                 | 50                 |
| RATED SPEED                            | 1500               | 1500               |
| RATED APPARENT POWER (PRP)             | 40                 | 60                 |
| RATED VOLTAGE 3PH.<br>LINE TO LINE (A) | 57.1               | 86.6               |
| ENGINE MAKE                            | DEUTZ              | DEUTZ              |
| MAKE                                   | BF4M 2011          | BF4M 2011C         |
| RATED NET OUTPUT (kW)                  | 36.4               | 55.2               |
| BASIC UNIT DIMENSIONS<br>(LxWxH) m     | 2.36 x 1.28 x 1.18 | 2.36 x 1.28 x 1.18 |
| WEIGHT (READY TO OPERATE) (kg)         | 1144               | 1144               |

Built and tested to ISO 9001 quality assurance standards.

**Notes:**





**Light tower**



# Light tower



|                                             | CPLT                                     |
|---------------------------------------------|------------------------------------------|
| ENGINE CHARACTERISTICS                      |                                          |
| MODEL                                       | Yanmar 2TNV70, 2 Cylinder Diesel engine  |
| POWER – kW                                  | 6.7                                      |
| FUEL TANK CAPACITY – US gal (l)             | 30 (113.6)                               |
| FUEL AUTONOMY – hour                        | 85                                       |
| EMISSIONS                                   | EPA Tier 4                               |
| ALTERNATOR CHARACTERISTICS                  |                                          |
| MODEL                                       | Permanent magnet brushless, LE G24N1-001 |
| RATED POWER – kVA                           | 5                                        |
| INSULATION CLASS                            | H                                        |
| TORCH CHARACTERISTICS                       |                                          |
| LAMPS                                       | 4 metal halide 1000 W lamps              |
| EXTERNAL BALLAST                            | No                                       |
| MAX. LIGHTING CAPACITY                      | 110.000 lumen/bulb                       |
| MAST CHARACTERISTICS                        |                                          |
| MAXIMUM HEIGHT – ft (m)                     | 31 (9.44)                                |
| ROTATION                                    | 360°                                     |
| OPERATION                                   | Manual                                   |
| MAXIMUM WIND SPEED – miles/h (km/h)         | 65 (105)                                 |
| DIMENSIONS AND WEIGHT L x W x H<br>inch (m) | 175 x 120 x 69 (4.45 x 3.04 x 1.75)      |
| WEIGHT – lbs (kg)                           | 1460 (662)                               |

\* Not sold within EU/EEU

**Notes:**



Notes:



[www.cp.com](http://www.cp.com)



## Over 100 years of experience

Since 1901 the name Chicago Pneumatic has stood for innovative, high-performance power tools. Today a wide range of pneumatic and hydraulic construction tools, including breakers, clay diggers, picks and busters, scabblers, rock drills, rotary and chipping hammers, sump and sludge pumps, and a whole lot more, are available through a worldwide sales organization.

For more detailed information, please contact:

Use only authorized parts. Any damage or malfunction caused by the use of unauthorized parts is not covered by Warranty or Product Liability.

